


Not All Coverage Measurements Are Equal

Fuzzing by Coverage Accounting for Input Prioritization

NDSS Symposium 2020

Yanhao Wang, Xiangkun Jia, Yuwei Liu, Kyle Zeng,

Tiffany Bao, Dinghao Wu, and Purui Su



AFL Family and Coverage-based Fuzzing



AFL



AFLFast



FairFuzz



CollAFL



AFL-Sensitive




QSYM



Driller

AFL Family and Coverage-based Fuzzing



Coverage-based Fuzzing: The Internals

Input Prioritization Factors:
Execution Time, Input Size, etc.

Queue




Queue Culling
(isFavor)




Prioritized Queue



Favored




Coverage Measurements are Treated Equally



Spend equal time on security-sensitive paths
and security-insensitive paths

Delay finding vulnerabilities

Anti-Fuzzing




Inject fake coverage measurements to mislead coverage-based fuzzers

What then?

do not

We  treat coverage measurements equally

Coverage Accounting



The prioritization of input reflects **security sensitivity**

Coverage Accounting

What should be the indicators?


function level

loop level

basic block level

Design a new queue culling scheme based on coverage accounting metrics

Loop Level



Incorrect looping condition is often the root cause of memory corruption vulnerabilities

Basic Block Level

```
1    shl    [rbp+var1], 4
2    mov    edx, [rbp+var1]
3    mov    eax, edx
4    shl    eax, 4
5    add    eax, edx
6    mov    [rbp+var1], eax
7    mov    rdx, [rbp+var2]
8    mov    rax, [rbp+i]
9    add    rax, rdx
10   movzx  edx, byte ptr [rax]
11   movzx  eax, [rbp+var3]
12   xor    eax, edx
13   movzx  eax, al
14   add    [rbp+var1], eax
15   movzx  edx, [rbp+var3]
16   mov    eax, edx
17   shl    eax, 3
```



1	shl	[rbp+var1], 4	
2	mov	edx, [rbp+var1]	read
3	mov	eax, edx	
4	shl	eax, 4	
5	add	eax, edx	
6	mov	[rbp+var1], eax	write
7	mov	rdx, [rbp+var2]	read
8	mov	rax, [rbp+i]	read
9	add	rax, rdx	
10	movzx	edx, byte ptr [rax]	read
11	movzx	eax, [rbp+var3]	read
12	xor	eax, edx	
13	movzx	eax, al	
14	add	[rbp+var1], eax	write
15	movzx	edx, [rbp+var3]	read
16	mov	eax, edx	
17	shl	eax, 3	

read
write

Design

Coverage Accounting Information



Queue




Queue Culling
(isFavor)



Prioritized Queue



Favored



Security-sensitive
prioritized input




Security-insensitive
prioritized input



Other input

TortoiseFuzz: Coverage-based Fuzzer with Coverage Accounting



TortoiseFuzz

TortoiseFuzz: Coverage-based Fuzzer with Coverage Accounting



The Hare and The Tortoise Story, Bedtime Story by Kids Hut
<https://www.youtube.com/watch?v=eMXmMHVNx4U>

Implementation

We implement **coverage accounting** on AFL as **TortoiseFuzz**

We implement **TortoiseFuzz** for both source code and binaries

Experiment Setup


We ran TortoiseFuzz on 30 real-world programs

Each experiment lasted for 140 hours

Each experiment was done 10 times


We performed Mann-Whitney U test to measure statistical significance

Vulnerability Discovery



TortoiseFuzz outperforms 5 state-of-the-art fuzzers and achieves comparable results with QSYM

Comparison with QSYM



TortoiseFuzz uses 2% of QSYM's memory usage on average

Complementary to Other Fuzzers


Coverage accounting helps improve QSYM in discovering vulnerabilities

Average # of discovered vulnerabilities	
QSYM	QSYM + coverage accounting
39.8	51.2




28.6% improvement

Robustness to Anti-fuzzing



Fake paths do not contain many coverage accounting info

Robustness to Anti-fuzzing



Coverage accounting metrics
are more robust to anti-fuzzing

Conclusion

We propose **coverage accounting** which is complementary to other coverage-based fuzzers

We design and implement **TortoiseFuzz**, and we are going to release it at <https://github.com/TortoiseFuzz/TortoiseFuzz>

We evaluate TortoiseFuzz on **30** real-world programs and find **20** zero-day vulnerabilities

TortoiseFuzz outperforms **5** state-of-the-art fuzzers and achieves comparable results with QSYM with **2%** of its memory usage

Not All Coverage Measurements Are Equal

Fuzzing by Coverage Accounting for Input Prioritization

Thank you!
Q & A

Kyle Zeng zengyhkyle@asu.edu